



Floor standing type

R410 | DC Inverter

MODEL		FGF - 481 EI/3JA - N2	
Capacity	kW	12,00	13,60
Capacity	Btu	40.944	46.403
Pdesign (C/A/W)*	kW	12,00	11,00
Capacity Range	kW	3,00 - 13,00	3,40 - 14,00
Capacity Range	Btu	10.236 - 44.356	11.600 - 47.768
Power Input (min-max)	kW	0,66 - 5,40	0,70 - 4,40
Current Input (nom-max)	A	6,00 (9,50)	6,50 (9,00)
Annual Consumption	kWh/ann	824	4053
SEER - SCOP(C/A/W) - Energy Class	W/W	5,10 A	./-3,80A/-
Ambient Temperature Range	°C	-15 ~ 43°C	
Power supply	V-Ph-Hz	400V ~ 3N - 50 Hz	
Power Connection Cable ODU.-IDU. / Com.	mm ²	5x2,5 - NO/ 4x1,5	
Compressor Type		MITSUBISHI DC Inverter Rotary	
Air Flow Volume	m ³ /h	1.850 / 1.800 / 1.700 / 1.530	
Sound Pressure Level IDU (H/M/L) - ODU.	dB(A)	52 / 50 / 48 / 45 - 63	
Sound Power IDU (H/M/L) - ODU	dB(A)	63 / 61 / 58 / 56 - 70	
Diameter Liquid-Gas Connection Pipe	inch	3/8" - 5/8"	
Refrigerant charge (precharge/after 5m)		R410a - 3,5kg / 50g/m	
Max Distance /Height Connection Pipe	m	25 / 10	
Indoor Unit Dimension LxHxD /Weight	mm/kg	580 x 400 x 1.870 / 58	
Outdoor Unit Dimension LxHxD /Weight	mm/kg	1.107 x 440 x 1.100 / 94	